

LOYAL™ Aluminium Industrial / Trade Scaffold Tower

Manufactured to BSEN 1004 (Class 3)
Aluminium Scaffold Tower (Double Width)

Tower Dimension : 1.45m(W) x 1.8m or 2.5m(L) x 5.7m(H)
Max. Platform Height : 4.7m, Max. Working Height : 6.7m

Maximum Working Load :
Tower - **950 kg** including tower self weight
Platform - **275 kg** when load uniformly distributed

| Item | Description | Qty. |
|------|---|------|
| 1. | Castor Wheel 200mm dia. W/Adj. Leg | 4 |
| 2. | 1450 2 Rung Ladder Frame 1.45 x 1.0m (1.0m) | - |
| 3. | 1450 2 Rung Span Frame 1.45 x 1.0m (1.0m) | - |
| 4. | 1450 3 Rung Ladder Frame 1.45 x 1.5m (1.5m) | 1 |
| 5. | 1450 3 Rung Span Frame 1.45 x 1.5m (1.5m) | 1 |
| 6. | 1450 4 Rung Ladder Frame 1.45 x 2.0m (2.0m) | 2 |
| 7. | 1450 4 Rung Span Frame 1.45 x 2.0m (2.0m) | 2 |
| 8. | Trapdoor Platform 600 x 1800 or 2500 | 2 |
| 9. | Fixed Platform 600 x 1800 or 2500 | 1 |
| 10. | Horizontal Brace 1800 or 2500 (Red) | 10 |
| 11. | Diagonal Brace 2100 or 2700 (Blue) | 8 |
| 12. | Folding Toeboard 1200 x 1800 or 2500 | 1 |
| 13. | Fixed Outrigger - Small | 4 |
| 14. | Telescopic Outrigger - Medium | - |
| 15. | Telescopic Outrigger - Large | - |

Scale : NTS

Weight : 177.1 kg or 207.9 kg

