

# LOYAL™ Aluminium Industrial / Trade Scaffold Tower

Manufactured to BSEN 1004 (Class 3)  
Aluminium Scaffold Tower (Double Width)

Tower Dimension : 1.45m(W) x 1.8m or 2.5m(L) x 6.2m(H)  
Max. Platform Height : 5.2m, Max. Working Height : 7.2m

**Maximum Working Load :**  
Tower - 950 kg including tower self weight  
Platform - 275 kg when load uniformly distributed

Item	Description	Qty.
1.	Castor Wheel 200mm dia. W/Adj. Leg	4
2.	1450 2 Rung Ladder Frame 1.45 x 1.0m (1.0m)	-
3.	1450 2 Rung Span Frame 1.45 x 1.0m (1.0m)	-
4.	1450 3 Rung Ladder Frame 1.45 x 1.5m (1.5m)	-
5.	1450 3 Rung Span Frame 1.45 x 1.5m (1.5m)	-
6.	1450 4 Rung Ladder Frame 1.45 x 2.0m (2.0m)	3
7.	1450 4 Rung Span Frame 1.45 x 2.0m (2.0m)	3
8.	Trapdoor Platform 600 x 1800 or 2500	2
9.	Fixed Platform 600 x 1800 or 2500	1
10.	Horizontal Brace 1800 or 2500 (Red)	10
11.	Diagonal Brace 2100 or 2700 (Blue)	9
12.	Folding Toeboard 1200 x 1800 or 2500	1
13.	Fixed Outrigger - Small	4
14.	Telescopic Outrigger - Medium	-
15.	Telescopic Outrigger - Large	-

Scale : NTS

Weight : 183.3 kg or 214.5 kg

