

LOYAL™ Aluminium Industrial / Trade Scaffold Tower

Manufactured to BSEN 1004 (Class 3)
Aluminium Scaffold Tower (Single Width)

Tower Dimension : 0.85m(W) x 1.8m or 2.5m(L) x 10.7m(H)
Max. Platform Height : 9.7m, Max. Working Height : 11.7m

Maximum Working Load :
Tower - **950 kg** including tower self weight
Platform - **275 kg** when load uniformly distributed

Item	Description	Qty.
1.	Castor Wheel 200mm dia. w/Adj. Leg	4
2.	850 2 Rung Ladder Frame 0.85 x 1.0m (1.0m)	1
3.	850 2 Rung Span Frame 0.85 x 1.0m (1.0m)	1
4.	850 3 Rung Ladder Frame 0.85 x 1.5m (1.5m)	1
5.	850 3 Rung Span Frame 0.85 x 1.5m (1.5m)	1
6.	850 4 Rung Ladder Frame 0.85 x 2.0m (2.0m)	4
7.	850 4 Rung Span Frame 0.85 x 2.0m (2.0m)	4
8.	Trapdoor Platform 600 x 1800 or 2500	3
9.	Horizontal Brace 1800 or 2500 (Red)	14
10.	Diagonal Brace 2100 or 2700 (Blue)	18
11.	Folding Toeboard 600 x 1800 or 2500	1
12.	Fixed Outrigger - Small	-
13.	Telescopic Outrigger - Medium	4
14.	Telescopic Outrigger - Large	-

Scale : NTS

Weight : 237.6 kg or 269.3 kg

