

LOYAL™ Aluminium Industrial / Trade Scaffold Tower

Manufactured to BSEN 1004 (Class 3)
Aluminium Scaffold Tower (Single Width)

Tower Dimension : 0.85m(W) x 1.8m or 2.5m(L) x 12.2m(H)
Max. Platform Height : 11.2m, Max. Working Height : 13.2m

Maximum Working Load :
Tower - **950 kg** including tower self weight
Platform - **275 kg** when load uniformly distributed

| Item | Description | Qty. |
|------|--|------|
| 1. | Castor Wheel 200mm dia. w/Adj. Leg | 4 |
| 2. | 850 2 Rung Ladder Frame 0.85 x 1.0m (1.0m) | - |
| 3. | 850 2 Rung Span Frame 0.85 x 1.0m (1.0m) | - |
| 4. | 850 3 Rung Ladder Frame 0.85 x 1.5m (1.5m) | - |
| 5. | 850 3 Rung Span Frame 0.85 x 1.5m (1.5m) | - |
| 6. | 850 4 Rung Ladder Frame 0.85 x 2.0m (2.0m) | 6 |
| 7. | 850 4 Rung Span Frame 0.85 x 2.0m (2.0m) | 6 |
| 8. | Trapdoor Platform 600 x 1800 or 2500 | 4 |
| 9. | Horizontal Brace 1800 or 2500 (Red) | 18 |
| 10. | Diagonal Brace 2100 or 2700 (Blue) | 21 |
| 11. | Folding Toeboard 600 x 1800 or 2500 | 1 |
| 12. | Fixed Outrigger - Small | - |
| 13. | Telescopic Outrigger - Medium | - |
| 14. | Telescopic Outrigger - Large | 4 |

Scale : NTS

Weight : 279.6 kg or 319.4 kg

