## A SAFER WAY TO REACH NEW HEIGHTS

## BS 8620:2016 PODIUM

Instruction/Safety Manual Self Closing
Mobile 1 Person Low Level Working Platform

Maximum safety working load 150 KG www.laddersandscaffoldtowers.co.uk

#### **Safety Information:**

**IMPORTANT:** 

Never use the BS 8620:2016 Podium LLWP

Until you have read the instructions fully and under- stood the following guide.

**ALWAYS** carry out a risk assessment for each task before you start work, to ensure the BS 8620:2016 Podium is the correct mode of access for the taskthat is being undertaken.

#### **Component List**

- 1 x Main frame
- 1 xAccessladder
- 1xPlatform
- 2 x Stabilisers

### Safety Checklist

- 1. Make sure that the equipment is in good working order.
- 2. The total load (person and equipment) must not exceed 150KG.
- 3. Make sure all castors are pointing outwards and locked correctly.
- 4. Always make sure the ladder is located in the correct position.
- 5. Ensure all components are present and correctly fitted before use.



BPS Access Solutions Unit 8 - Highams Hill Farm Sheepbarn Lane Warlingham Surrey CR6 9PQ



Tel: 03330069776

Email: sales@bpsaccesssolutions.co.uk



KM 642952



# **EQUIPMENT MAINTENANCE**

- ✓ ChecktheBS 8620:2016 Podium LLWP main frame is not bent, twisted, dented and has no cracked welds.
- ✓ Check that fixings (usually weld rivets or bolts) are good, appropriate, not missing, loose.
- ✓ Check That components are not missing, loose, worn or damaged.
- ✓ Check that the locking mechanisms are operating locking correctly. Ladder hinge elbow locking joints platform clips are not broken.
- ✓ Check all caster wheels operate.
- ✓ Checkthattheentire BS 8620:2016 Podium LLWP is free from containments (e.g. dirt, mud, paint oil or grease)
- ✓ Check that the platform has no missing parts or fixings and is not damaged.

# DO'S AND DONT'S



# IMPORTANT: Never climb on the BPS BS8620 podium (LLWP) until you have checked the following:


Theladderissecureandpositionedcorrectly.

The platform is secure and positioned correctly.


All castors/baseplates and stabilisers are positioned correctly.

The folding back section is locked.

**1.**With the podium step in a closed position, ensure all castors are locked



**4.**Position ladder on to lower rung and push down making sure ladder hooks are locked within the guides. Now do the same to the top of the ladder




**7.** Stabiliser to be securely fixed to the podium by tightening the palm wheel and coupler.



2. Open Rear frames and lock the locking elbow joints into position



**5.**Make sure the castors are at a 45-degree angle and then lock into place




8. Move the gate from the locked position and secure it behind you.


Make sure it is locked, never use the podium without locking the gate



**3.**Square and position the platform at the chosen height and turn the wind lock to the closed position



**6.**Fit podium stabilisers at a 45-degree angle (see photo A) Unless against a wall (see photo B) Making sure stabiliser is located on the floor



**9.** Using the ladder, climb onto the podium platform

